



104 Key Panel Mount Keyboard

The INDUCOMP panel mount 104 key industrial keyboard is made of elastomeric rubber which provides great tactile feel. Keyboards can be ordered to meet NEMA 4, 4X or 12 specifications. All keyboards can include a rugged elastomeric pointing device. No matter what the application, INDUCOMP's rugged industrial keyboards can withstand the harshest environments.



Material	Industrial Elastomeric Rubber
Life Cycle	Greater than 10 million cycles
Travel	0.080 in. (2mm)
Actuation Force	5 oz. (130g)
Feedback	Tactile with Mechanical Snap
Power	5V@20 mA (from CPU port)
Temperature	-40 F to + 194 F (-40 C to +90 C)
Humidity	100% Humidity Resistant
Shock	3 x 11 ms pulse of 50g on each of 3 axes
Vibration	Power spectral Density: .04g/HZ

Frequency Range	20Hz-2Khz
Test Duration per Axis	3 hours
Flammability	Elastomeric Overlay: 94HB; Circuit Board: 94VO, Cable: 94VO
Dimensions	(W-H-D) 20.5" x 9.8" x 0.6"
Compatibility	AT, PS/2, pointing device PS/2 or RS-232 DB9
Features	Meets NEMA 4, 4X and 12 specifications
Dimensions	(W-H-D) 20.5" x 9.8" x 0.6"

INDUCOMP Corporation
Phone: 636-257-2111 Fax: 636-257-2332
<http://www.inducomp.com>